



PARÇA NO ITEM NO.	PARÇA ADI ITEM DISCRPTION	MALZEME MATERIAL		
20	PLASTİK KAPLAMA PLASTIC COVERING	PVC	PVC	
19	KÜRE HAREKET KOLU BALL ACTION HANDLE	st 37	1.4301.	
18	CİVATA BOLT	ST 42 Gal.	1.4301. - 1.4401.	
17	STOPLAMA PİMİ STOPPING PIM	ST 42 Gal.	1.4301.	
16	ANTİSTATİK KÜRE ANTISTATIC BALL	1.4301.	1.4301. - 1.4401.	
15	ANTİSTATİK YAY ANTISTATIC SPRING	1.4301.	1.4301. - 1.4401.	
14	SOMUN NUT	5.6.	1.4301. - 1.4401.	
13	SAPLAMA STOPPING PIM	4140 - 514t	1.4301.	
12	KONTRA SOMUN COUNTER NUT	5,6 Gal.	1.4301.	
11	ÇANAK PUL BOWL WASHER	50 Cr V 4	1.4301.	
10	BASKI RİNGİ PRESSURE RING	MS 58	1.4301. - 1.4401.	
9	MİL O-RİNG SPINDLE O-RING	VİTON	VİTON	
8	BURGMAN GRAFİT O-RİNG BURGMAN GRAPHITE O-RING	EN 1514-1	EN 1514-1	
7	BOĞAZ SIZDIRMAZLIK TEFLONU NECK TIGHTNESS ELEMENT	PTFE-Teflon	PTFE-Teflon	
6	GÖVDE SIZDIRMAZLIK TEFLONU BODY TIGHTNESS ELEMENT	PTFE-Teflon	PTFE-Teflon	
5	KÜRE SIZDIRMAZLIK TEFLONU BALL TIGHTNESS ELEMENT	PTFE-Teflon	PTFE-Teflon	
4	HAREKET MİLİ ACTION SPINDLE	1.4021	1.4301. - 1.4401.	
3	KÜRE BALL	1.4301 / 1.4086	1.4305. - 1.4401.	
2	KAPAK COVER	SAE 1020	1.4301. - 1.4401.	
1	GÖVDE BODY	SAE 1020	1.4301. - 1.4401.	

Boyut Dimensions : BATUSAN ÖZEL  
 Bağlantılar Connections : EN 10226-1  
 Çalışma Basıncı Working Pressure : PN 100  
 Çalışma Sıcaklığı Working Temperature : -30 °C / +180 °C

Kullanım Alanları Usege Areas :  
 Su, Sıcak Su, Buhar, Basıncılı Hava  
 Water, Hot Water, Steam, Pressurized Air


**BOYUT ve BAĞLANTI ÖLÇÜLERİ DIMENSIONS AND CONNECTION SIZES**

		PN 100						
		L	G	H	d	D	t	Kg
DN 15	1/2"	110	150	75	15	1/2"	14	--
DN 20	3/4"	130	150	83	20	3/4"	17	--
DN 25	1"	145	180	90	25	1"	20	--
DN 32	1 1/4"	160	230	95	32	1 1/4"	22	--
DN 40	1 1/2"	170	275	115	40	1 1/2"	25	--
DN 50	2"	185	275	120	50	2"	28	--