

## Çift Etkili Pnömatik Aktuatörler



**ÇİFT ETKİLİ PNÖMATİK AKTÜATÖR TORK DEĞERLERİ (Nm)**

MODEL	Besleme Hava Basıncı (bar)											
	2.5	3	3.5	4	4.5	5	5.5	6	6.5	7	7.5	8
T-RPA DA 32	2.0	3	4.0	5	6.0	7	8.0	9	10.0	11	12.0	13
T-RPA DA 40	7.5	9	10.5	12	13.5	15	16.5	18	19.5	21	22.5	24
T-RPA DA 60	14	18	22	26	30	34	38	42	46	50	54	58
T-RPA DA 80	26	38	50	62	74	86	98	110	122	134	146	158
T-RPA DA 100	73	88	103	118	133	148	163	178	193	208	223	238
T-RPA DA 120	137.5	165	192.5	220	247.5	275	302.5	330	357.5	385	412.5	440
T-RPA DA 143	240	288	336	385	433	480	529	578	626	674	722	770
T-RPA DA 160	321	385	450	510	576	642	705	765	833	897	963	1024
T-RPA DA 200	628	752	878	1000	1127	1252	1377	1500	1630	1752	1880	2005
T-RPA DA 400	1214	1454	1697	1933	2178	2420	2662	2900	3154	3378	3634	3876

AKTÜATÖR TİP NO	Açmada Hava Debisi (L)	Kapamada Hava Debisi (L)	Açma Süresi (Sn.)	Kapama Süresi (Sn.)	Ağırlık (kg)	
T-RPA DA/SR 40	DA	0.09	0.16	0.22	0.26	0.85
	SR			0.26	0.34	1.02
T-RPA DA/SR 60	DA	0.17	0.28	0.27	0.33	1.70
	SR			0.33	0.38	1.80
T-RPA DA/SR 80	DA	0.50	0.79	0.39	0.48	3.80
	SR			0.48	0.57	4.40
T-RPA DA/SR 100	DA	0.73	1.15	0.52	0.63	4.90
	SR			0.63	0.95	6.10
T-RPA DA/SR 120	DA	1.61	2.45	0.95	1.15	9.60
	SR			1.15	1.47	11.40
T-RPA DA 143	DA	2.85	1.95	2.40	2.20	13.00
T-RPA DA 160	DA	3.25	2.56	2.60	2.30	19.10
T-RPA DA 200	DA	6.41	5.50	3.40	3.20	33.40
T-RPA DA 400	DA	12.60	10.80	4.30	3.90	72.00
T-RPA SR 143	SR	2.85	4.70	3.20	3.00	17.60
T-RPA SR 160	SR	3.25	5.36	3.80	3.50	26.80
T-RPA SR 200	SR	6.41	10.50	4.80	4.40	45.90
T-RPA SR 400	SR	12.60	20.79	5.90	5.20	98.00

