



PARÇA NO ITEM NO	PARÇA ADI ITEM DISCRPTION	MALZEME MATERIAL
19	PLASTİK KAPLAMA PLASTIC COVERING	PVC PVC
18	KÜRE HAREKET KOLU BALL ACTION HANDLE	st 37 1.4301.
17	ANTİSTATİK KÜRE ANTISTATIC BALL	1.4301. 1.4301. - 1.4401
16	ANTİSTATİK YAY ANTISTATIC SPRING	1.4301. 1.4301. - 1.4401
15	CİVATA BOLT	ST 42 Gal. 1.4301. - 1.4401
14	STOPLAMA PİMİ STOPPING PIM	ST 42 Gal. 1.4301.
13	KONTRA SOMUN COUNTER NUT	5,6 Gal. 1.4301.
12	ÇANAK PUL BOWL WASHER	50 Cr V 4 1.4301.
11	BASKI RİNGİ PRESSURE RING	MS 58 1.4301. - 1.4401
10	MİL O-RİNG SPINDLE O-RING	VİTON VİTON
9	BURGMAN GRAFİT O-RİNG BURGMAN GRAPHITE O-RİNG	EN 1514-1 EN 1514-1
8	BOĞAZ SIZDIRMAZLIK TEFLONU NECK TIGHTNESS ELEMENT	PTFE-Teflon PTFE-Teflon
7	GÖVDE O-RİNG BODY O-RING	VİTON VİTON
6	GÖVDE SIZDIRMAZLIK TEFLONU BODY TIGHTNESS ELEMENT	PTFE-Teflon PTFE-Teflon
5	KÜRE SIZDIRMAZLIK TEFLONU BALL TIGHTNESS ELEMENT	PTFE-Teflon PTFE-Teflon
4	HAREKET MİLİ ACTION SPINDLE	1,4021 1.4301. - 1.4401
3	KÜRE BALL	1.4301 / 1.4086 1.4301. - 1.4401
2	KAPAK COVER	ASTM A 105 1.4301. - 1.4401
1	GÖVDE BODY	ASTM A 105 1.4301. - 1.4401

Boyut Dimensions : BATU ÖZEL
Bağlantılar Connections : ASME B 16.5
Çalışma Basıncı Working Pressur : CLASS 150 (PN 20)
CLASS 300 (PN 50)
Çalışma Sıcaklığı Working Temperature : -30 °C / +250 °C

Kullanım Alanları Usege Areas :
Doğalgaz, LPG-LNG, Fuel-Oil, Basıncılı Hava ve Diğer Gazlar
Natural Gas, LPG-LNG, Fuel-Oil, Pressurized Air and Other Gases etc.



BOYUT ve BAĞLANTI ÖLÇÜLERİ DIMENSIONS AND CONNECTION SIZES

	L	G	H	f	D	CLASS 150 (PN 20)				CLASS 300 (PN50)				Kg
						k	Hole Unit	M	F	k	Hole Unit	M	F	
DN 15 1/2"	38	150	75	2	90	60,0	4	M 12	35,1	66,7	4	M 12	35,1	--
DN 20 3/4"	40	150	83	2	97	70,0	4	M 12	42,9	82,6	4	M 16	42,9	--
DN 25 1"	45	180	90	2	107	79,4	4	M 12	50,8	88,9	4	M 16	50,8	--
DN 32 1 1/4"	58	230	95	2	118	89,0	4	M 12	63,5	98,4	4	M 16	63,5	--
DN 40 1 1/2"	64	275	115	2	128	98,4	4	M 12	73,2	114,3	4	M 20	73,2	--
DN 50 2"	82	275	120	2	158	120,6	4	M 16	91,9	127,0	8	M 16	91,9	--
DN 65 2 1/2"	103	320	135	2	177	139,7	4	M 16	104,6	149,2	8	M 20	104,6	--
DN 80 3"	122	380	150	2	188	152,4	4	M 16	127,0	168,3	8	M 20	127,0	--
DN 100 4"	150	450	170	2	227	190,5	8	M 16	157,2	200,0	8	M 20	157,2	--
DN 125 5"	200	450	200	2	270	216,0	8	M 20	185,7	235,0	8	M 20	185,7	--
DN 150 6"	235	650	235	2	305	241,3	8	M 20	215,9	269,9	12	M 20	215,9	--
DN 200 8"	310	900	270	2	400	298,4	8	M 20	269,7	330,2	12	M 22	269,7	--